

# FR8 Fingerprint Digital ANSI Mortise Door Lock

- An aesthetic design adds style to enhance household quality.
- Available for ANSI & EN mortise lockset.


## ANSI Mortise Lock

- US ANSI Grade 1
- UL 10C - 3 hours fire rating



## EN Mortise Lock

- EN 179:2008 - Emergency exit
- EN 1634-1:2004 - Fire rated up to 4 hours.
- EN 12209:2003/ AC:2005 - Building hardware. Lock and latch. Mechanically lock, latch, and locking plate.
- EN14846:2008 - Building hardware. Lock and latch. Electromechanically operated lock, latch, and locking plate.



## Multiple Access

- Fingerprint, PIN Code, and Key Override.

## Fingerprint

- An aesthetic design adds style to enhance household quality.
- It can identify both dry and wet fingerprints.
- Biological scanning: physical fingerprint identification (optional)
- 360° fingerprint identification.

## Hold Open Mode

- The lock can be set between 1 to 999 minutes to remain unlocked when people need to go in and out consistently.

## Two Administration Modes

- EZ mode
  1. ONE user code is available.
  2. One-time user code is not available.
  3. Keypad sound cannot be turned off.
- Normal mode
  1. Maximum 200 user codes.
  2. One-time user code is available.
  3. Keypad sound can be turned off.

## Prank Warning

- The lock will be disabled after entering 10 times of incorrect user codes or fingerprints consecutively to prevent trespassing.

## Concealed Key Override



## Low Battery Warning

- If the batteries are running low, the door lock informs you through keypad with a digit for entry times left, also beep and blink \* 3 times.

## SPECIFICATIONS

Capacity	50 users	Door Thickness	40 to 80 mm
Outer Body	84x208x76 mm (WxHxD)	Backset	70 mm
Inner Body	96x230x73 mm (WxHxD)	Power Supply	4 AA alkaline 1.5V batteries (6V)
Lockset Type	ANSI mortise, EN mortise (optional)	Battery Life	up to 12 months
Finish	US26D	Working Temperature	-20°C to 70°C (-4°F to 158°F)